LIFT & SLIDE

TOTAL FACADE SOLUTIONS

DOUBLE GLAZING **Uw=1,3** W/m²K

TRIPLE GLAZING **Uw=0,85** W/m²K

Material	Wood-Aluminium	
Thermal insulation	Uw= 1,3 W/m²K	Uw= 0,85 W/m²K
Insulating glass	Double glazing thickness 32 mm	Triple glazing thickness 52 mm
Acoustic insulation	Not declared	
Security hardware	Up to RC2	

Air permeability	CLASS 4
Water tightness	CLASS 9A
Wind load resistance	CLASS B5

The thermal transmittance values are calculated according to UNI EN 10077/1-2018, UNI EN 10077/2-2018, UNI EN 10456-2008, UNI EN 673-2011 standards, in reference to a lift-sliding door Plan A - WxH (2800x2500mm, ψg= 0,04 W/mK)

The air-water-wind tightness performances are estimated in reference to a lift-sliding door Plan A - WxH (2800x2500mm)

HS-MAGIS40 - 32 mm glass SOFT WOOD

Ug W/m²K		**Uw** W/m²K
1,0	-»	1,3
1,1	-»	1,4
1,2	-»	1,5
1,3	-»	1,6
1,4	-»	1,7
1,5	-»	1,8
1,6	-»	1,8

HS-MAGIS40 - 52 mm glass SOFT WOOD

Ug W/m²K		**Uw** W/m²K
0,5	-»	0,85
0,6	-»	0,95
0,7	-»	1,0
0,8	-»	1,1
0,9	-»	1,2
1,0	-»	1,3
1,1	-»	1,4

TOTAL FACADE SOLUTIONS

748 Marine Dr,
North Vancouver, BC

778 729 1575
contact@totalproject.ca